


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) [more »](#)


[Advanced Search](#)
[Preferences](#)

[Get the Google Toolbar](#)

Web Results 1 - 6 of 6 for **drag viv vortex vibration roughness surface ks/d OR k/d**. (0.25 seconds)

Tip: Save time by hitting the return key instead of clicking on "search"

[PDF] [Microsoft PowerPoint - Some of the VIV R&D Activities at Shell.ppt](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

VIV suppression general. • Fairings. • Strakes. • **Surface roughness** ...

Allen, DW, Henning DL, and Lee, L., 2004, "**Vortex-induced vibration** current tank ...

www.marin.ntnu.no/~callas/workshop/VIVW_Lee_Shell.pdf - [Similar pages](#)

[Sleeve or coating - Patent Storm](#)

Apparatus for controlling **drag** and **vortex-induced vibration** exerted onto a ...

having a **surface roughness** coefficient of **K/D** less than or equal to 1×10^{-4} , ...

www.patentstorm.us/class/405/216-Sleeve_or_coating.html - 34k - [Cached](#) - [Similar pages](#)

[PDF] [DIS Submission to ISO CS 2004-08-31](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

A.9.5.2.3.2 **Surface roughness**. The dependence of the steady-flow **drag** coefficient at

... response called **vortex induced vibration (VIV)** can occur. ...

www.galbraithconsulting.co.uk/iso/19902/DIS_text/19902_Clause_09_DIS.pdf - [Similar pages](#)

[PDF] [W OrcaFlex Manual](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 59 3.13.1 Example RAO Text File 59 3.14 M - **VIV** 59 3.14.1 M01 **Vortex** Tracking 59

4 USER INTERFACE 61 ... 174 6.10.18 **Drag** Chains 176 6.10.19 Line End Conditions ...

www.orcina.co.uk/OrcaFlex/OrcaFlex.pdf - [Supplemental Result](#) - [Similar pages](#)

[PDF] [W OrcaFlex Manual](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 4 3.13.1 Example RAO Text File 61 3.14 M - **VIV** 61 3.14.1 M01 **Vortex** Tracking 61

4 USER INTERFACE 63 ... 184 6.10.18 **Drag** Chains 186 6.10.19 Line End Conditions ...

www.orcina.co.uk/OrcaFlex/OrcaFlex_US_paper_size.pdf - [Supplemental Result](#) - [Similar pages](#)

[00databasealphabet I+pw u 00data seinfo B0 FL 00databasescript I+ ...](#)

... BQ9G y carat BQ94 T caravan BQ+L Z cavel BQ+k d caraway BQ/B i carbamide BQ/j

... U **surface** HqHR BP **surface** finish Hqig 7 **surface** plate Hqjb w **surface** ...

users.csu.ac.ru/~srg/links/sokrat_c.html - 970k - [Cached](#) - [Similar pages](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied? Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) [more »](#)

[Advanced Search](#)
[Preferences](#)

Web Results 11 - 20 of about 22 for **drag smooth cylinder vortex vibration ks/d OR k/d "surface roughness"**

[PDF] [MANEUVERING AND CONTROL OF MARINE VEHICLES](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 53 7.3.4 Heeling in Submarines with Sails 54 8 STREAMLINED

BODIES 56 8.1 Nominal **Drag** Force

www.twocw.net/.../ 9902D412-8BF9-4401-874B-850F2FC6267A/0/all.pdf - Supplemental Result - [Similar pages](#)

[PDF] [Fluid Mechanics](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Boundary Layers • **Drag** • Lift • Boundary ... Experimental Techniques • **Surface Roughness**, Adhesion, and ... fluid-filled circular **cylinder** rotating uniformly ...

www.bgu.ac.il/~yakhot/mf2/Fluid_Dynamics.pdf - Supplemental Result - [Similar pages](#)

[PDF] [yyy 487 2001 Fall Exhibitor ONLINE PUBLICATIONS SYMPOSIUM Z Making ...](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Exhibition Hall D (Hynes) CONTROLLED SYNTHESIS OF CARBON NANOSTRUCTURES WITH **CYLINDER-ON-CONE** SHAPE. Vladimir I. Merkulov, Instrumentation ...

lucy.mrs.org/meetings/fall2001/ abstracts/AbstractBookZ.pdf - Supplemental Result - [Similar pages](#)

[PDF] [Flow Separation on Wind Turbine Blades](#)

File Format: PDF/Adobe Acrobat

... For example, the delay in the stall angle by **vortex** generators can be measured ... flags that are pressure driven while tufts are driven by frictional **drag**, which means ...

afrodite.upf.tche.br/incoming/rubens/full.pdf - Supplemental Result - [Similar pages](#)

[PDF] [AERC 2003](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Page 1. Programme & Abstracts Department of Polymer Engineering University of Minho AERC 2003 EUROPEAN SOCIETY OF RHEOLOGY Portuguese Society of Rheology ...

www.rheology-esr.org/.../Abstracts/AERC2003_symposiums.pdf?

PHPSESSID=091bf71cb79c004dc4f683ff493547c - Supplemental Result - [Similar pages](#)

[PDF] [Modern Manufacturing](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... For example, generally achievable **surface roughness** for sand casting is ... stiffness that are subject to **vibration** and chatter. ... feeds, but for a **smooth** finish the ...

www.itiomar.it/publica/dispense/ MECHANICAL%20ENGINEERING%20HANDBOOK/Ch13.pdf - Supplemental Result - [Similar pages](#)

[PDF] [W OrcaFlex Manual](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 59 3.14 M - VIV 59 3.14.1 M01 **Vortex** Tracking 59 4 USER INTERFACE ... 151 6.9.2 RAO Quality Checks 152 6.9.3 **Drag** Loads 154 6.9.4 Stiffness, Added Mass and Damping ...

www.orcina.co.uk/OrcaFlex/OrcaFlex.pdf - Supplemental Result - [Similar pages](#)

[PDF] [W OrcaFlex Manual](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 61 3.14 M - VIV 61 3.14.1 M01 **Vortex** Tracking 61 4 USER INTERFACE ... 159 6.9.2 RAO Quality Checks 161 6.9.3 **Drag** Loads 162 6.9.4 Stiffness, Added Mass and Damping ...

Checks 161 6.9.3 **Drag** Loads 162 6.9.4 Stiffness, Added Mass and Damping ...

Control of Circular Cylinder Flow by the Use of Dimples

P. W. Bearman* and J. K. Harvey†

Imperial College of Science, Technology and Medicine, London SW72BY, England, United Kingdom

Measurements are reported of the drag coefficient and Strouhal number of a dimpled circular cylinder over the Reynolds number range from 2×10^4 to 3×10^5 . The ratio of the depth of the dimples to the diameter of the cylinder is 9×10^{-3} . In common with sand-roughened cylinders, the dimpled cylinder has a lower critical Reynolds number than a smooth cylinder. After the drag coefficient minimum, the C_D does not rise to the high values that are typical of cylinders with sand roughness but is found to be closer to that for a smooth cylinder. Over a Reynolds number range from about 4×10^4 to 3×10^5 , a dimpled circular cylinder has a lower drag coefficient than a smooth cylinder.

Introduction

A CIRCULAR cylinder generates a high mean drag and large fluctuating forces. Over the last 40 years or so a considerable number of investigations have been carried out to study ways of reducing these forces, either by controlling the flow passively or by using some form of active control. Among the passive control devices that have been studied are wake splitter plates¹ and perforated shrouds.² The latter device has been used to suppress flow-induced vibration of cylinders caused by the regular shedding of vortices. The fitting of helical strakes³ is another means of reducing the vibration levels of circular cylinders excited by vortex shedding. However, a major disadvantage of using strakes is that they increase the drag force above the equivalent value for a plain cylinder. This increase is particularly large at postcritical Reynolds numbers. Perforated shrouds are interesting in that they reduce the drag coefficient, relative to a plain cylinder, at subcritical Reynolds numbers but they increase it at postcritical values.

There is a broad range of Reynolds number, spanning the transition between the subcritical and postcritical regimes and stretching far above it, where the flow around a circular cylinder can be influenced significantly by increasing the roughness of its surface. For a cylinder with a smooth surface, placed in a low-turbulence level stream, the start of the drag coefficient fall, marking the beginning of the critical regime, occurs at a Reynolds number of around 3×10^5 . At Reynolds numbers below this value, the application of an appropriate degree of surface roughness can be a very effective means of reducing the drag coefficient. However, as shown by Achenbach,⁴ the reduction in C_D for a rough cylinder at the Reynolds number is increased through the critical regime less than that for one with a smooth surface. In general, the rougher the cylinder surface, the lower the value of the critical Reynolds number, but the smaller the fall in C_D through the critical regime. Achenbach also showed that in the high Reynolds number postcritical regime a cylinder with a rough surface finish has a higher drag coefficient than one with a smooth surface.

The flow around a sphere depends on surface roughness in a manner very similar to the way roughness affects the flow around a circular cylinder. As part of an investigation into the aerodynamics of golf balls, Bearman and Harvey⁵ compared their measurements of the variation of C_D with Reynolds number for a dimpled golf ball with measurements of Achenbach⁶ for spheres with sand-grain roughness. The comparison is reproduced in Fig. 1. Achenbach carried out a series of experiments for spheres with various ratios of the average diameter

of the sand grains k to the sphere diameter D . It can be seen from Fig. 1 that, for sand-roughened spheres, increasing k/D reduces the Reynolds number for the drag coefficient fall but that after the minimum the C_D increases rapidly again with increasing Reynolds number. The increased C_D with increased surface roughness in the postcritical regime is thought to be due mainly to the effect of the roughness on the development of the turbulent boundary layer growing on the sphere. Compared with a smooth surface, the roughness causes a thickening of the boundary layer, which leads to an earlier separation of the flow. Equating k to the depth of the dimples on a golf ball, then for a typical golf ball the corresponding value of k/D is 9×10^{-3} . For similar values of k/D , the results in Fig. 1 suggest that dimples cause the C_D to fall at a lower Reynolds number than for a sand-roughened sphere. Also it is evident that after this fall the drag coefficient remains almost constant at about 0.25 for the golf ball, whereas for the sand-roughened sphere it rises sharply after the minimum and asymptotes to a value of about 0.4. Hence, by considering drag coefficient values, it appears that in the postcritical regime the dimples have a more beneficial effect on the flow development than sand roughness.

The present paper describes the results of experiments to assess the effect of dimples on the flow around a circular cylinder as it undergoes transition from subcritical to postcritical flow. The main aim of the investigation was to determine whether dimples can be used to control the flow in the same way as on a sphere. This paper has been prompted by a recent experimental and computational study reported by Kimura and Tsutahara⁷ on the effect of spanwise grooves on the flow around a circular cylinder. The width and depth of the grooves, relative to the diameter of the cylinder, were chosen to be similar to the diameter and depth of dimples on a golf ball. In their experiments, which were carried out at a Rey-





Fig. 1 Variation of C_D with Reynolds number for smooth and sand-roughened spheres and a golf ball.

Received June 9, 1992; revision received Jan. 27, 1993; accepted for publication Feb. 1, 1993. Copyright © 1993 by the American Institute of Aeronautics and Astronautics, Inc. All rights reserved.

*Professor and Head, Department of Aeronautics, Member AIAA.

†Professor, Department of Aeronautics, Member AIAA.



Web Results 1 - 10 of about 28 for **drag vortex vibration ks/d OR k/d "surface roughness"**. (0.41 seconds)

Tip: Save time by hitting the return key instead of clicking on "search"

[RTF] FLOW PAST CIRCULAR CYLINDERS WITH LONGITUDINAL CAVITIES; MOTIVATED ...

File Format: Rich Text Format - [View as HTML](#)

Surface roughness has been argued an unlikely adaptation to control **drag**, ...

The cylinders with cavities had lower CD values than the rough **ks/d** ...

me.stanford.edu/globals/cavitypaper.rtf - [Similar pages](#)

Sleeve or coating - Patent Storm

Apparatus for controlling **drag** and **vortex**-induced **vibration** exerted onto a ...

having a **surface roughness** coefficient of **K/D** less than or equal to 1×10^{-4} , ...

www.patentstorm.us/class/405/216-Sleeve_or_coating.html - 34k - [Cached](#) - [Similar pages](#)

[PDF] Microsoft PowerPoint - Some of the VIV R&D Activities at Shell.ppt

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Surface roughness effects. **k/D**: $7E-6$ to $1E-4$... Allen, DW, Henning DL, and Lee, L., 2004, "**Vortex**-induced **vibration** current tank tests of two equal ...

www.marin.ntnu.no/~callas/workshop/VIVW_Lee_Shell.pdf - [Similar pages](#)

[PDF] Control of Circular Cylinder Flow by the Use of Dimples

File Format: PDF/Adobe Acrobat

surface roughness can be. a. very effective means of reducing. the **drag** coefficient.

... the **drag** and the **vortex**-shedding frequency of a circular cylin- ...

pdf.aiaa.org/GetFileGoogle.cfm?glD=11844&gTable=japaperimportPre97 - [Similar pages](#)

[PDF] Experimental investigation of **surface roughness** generated flow noise

File Format: PDF/Adobe Acrobat

the subsequent dipole generated sound with the fluctuating **drag** ... of the effects of **surface roughness** on the noise production in ...

pdf.aiaa.org/GetFileGoogle.cfm?glD=54659&gTable=mtgpaper - [Similar pages](#)

[[More results from pdf.aiaa.org](#)]

[PDF] DIS Submission to ISO CS 2004-08-31

File Format: PDF/Adobe Acrobat - [View as HTML](#)

A.9.5.2.3.2 **Surface roughness**. The dependence of the steady-flow **drag** coefficient at

... response called **vortex** induced **vibration** (VIV) can occur. ...

www.galbraithconsulting.co.uk/iso/19902/DIS_text/19902_Clause_09_DIS.pdf - [Similar pages](#)

[PDF] BOUNDARY-LAYER STABILITY AND TRANSITION

File Format: PDF/Adobe Acrobat

effects of the **vortex** array. This latter flow field is further ... it by external turbulence, **surface roughness**, noise, and **vibration**," and that "the ...

arjournals.annualreviews.org/doi/abs/10.1146/annurev.fl.08.010176.001523 - [Similar pages](#)

[PDF] BOUNDARY-LAYER TRANSITION

File Format: PDF/Adobe Acrobat

to a time dependence of the **vortex** system such that the vorticity is most ...

Surface roughness is known to affect transition because of the disturb- ...

arjournals.annualreviews.org/doi/pdf/10.1146/annurev.fl.01.010169.001125 - [Similar pages](#)

[PDF] **SUBSEA PIPELINE SYSTEMS AND RISERS**

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Page 1. GUIDE FOR BUILDING AND CLASSING SUBSEA PIPELINE SYSTEMS AND RISERS

MARCH 2001 American Bureau of Shipping Incorporated by ...

www.eagle.org/rules/downloads/64-PRISER.pdf - Supplemental Result - [Similar pages](#)

[t0 EA000080_vn 2.2_pd 19950928_t1 EA000080 00223093_jn ...](#)

When the gauge head axis is vertical the magnetic **drag** on the rotating ...

Film surfaces were very smooth with average **surface roughness** 1.6 nm for 70 nm ...

web.mit.edu/afs/dev.mit.edu/project/libdevo/sun4/tulip/toc2sgml/EA000080.TOC - 513k - [Cached](#) - [Similar pages](#)

Google ►

Result Page: 1 2 3 [Next](#)



Google Desktop Search



9:30 AM

Free! Instantly find your email, files, media and web history. [Download now.](#)


drag vortex vibration ks/d OR k/d "s

Search

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied?](#) [Help us improve](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google



Web Results 11 - 20 of about 28 for **drag vortex vibration ks/d OR k/d "surface roughness"**. (0.27 seconds)

[PDF] Unsteady airfoil flows with application to aeroelastic stability

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Results indicate that using a transition model the **drag** prediction is improved ... leading edge separation which again will affect the overall **vortex** shedding. ...

www.forskningscenter.dk/rispubl/VEA/veapdf/ris-r-1116.pdf - Supplemental Result - [Similar pages](#)

[PDF] Technical and Research Bulletin 5-5A

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 4.2.2 **Drag** and inertia coefficients valid for the flow regime and chosen wave ... b)
 The magnitude of this **vibration** is primarily influenced by the amount of wave ...

www.sname.org/committees/offshore/OC-7/downloads/T_R%205-5A.pdf - Supplemental Result - [Similar pages](#)

[PDF] Flow Separation on Wind Turbine Blades

File Format: PDF/Adobe Acrobat

... For example, the delay in the stall angle by **vortex** generators can be measured ... flags are pressure driven while tufts are driven by frictional **drag**, which means ...

afrodite.upf.tche.br/incoming/rubens/full.pdf - Supplemental Result - [Similar pages](#)

[PDF] MANEUVERING AND CONTROL OF MARINE VEHICLES

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 53 7.3.4 Heeling in Submarines with Sails 54 8 STREAMLINED BODIES 56 8.1 Nominal **Drag** Force

www.twocw.net/.../9902D412-8BF9-4401-874B-850F2FC6267A/0/all.pdf - Supplemental Result - [Similar pages](#)

[PDF] yyy 487 2001 Fall Exhibitor ONLINE PUBLICATIONS SYMPOSIUM Z Making ...

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Page 1. y y y 487 * Invited paper 2001 Fall Exhibitor ONLINE PUBLICATIONS SYMPOSIUM
 Z Making Functional Materials with Nanotubes Chairs Patrick Bernier ...

lucy.mrs.org/meetings/fall2001/abstracts/AbstractBookZ.pdf - Supplemental Result - [Similar pages](#)

[PDF] THE SE WA GE PU MPI NG HAN DBO OK

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Page 1. T H E SE WA GE PU MPI NG HAN DBO O K Page 2. Foreword 3 The use of submersible pumps in sewage and drainage pumping applications ...

[www.grundfos.kz/web/grfosweb.nsf/GrafikOpslag/wastewater_brochures2/](http://www.grundfos.kz/web/grfosweb.nsf/GrafikOpslag/wastewater_brochures2/$File/ww_sewage_pumping_handbook.pdf)

[\\$File/ww_sewage_pumping_handbook.pdf](#) - Supplemental Result - [Similar pages](#)

[PDF] AERC 2003

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Page 1. Programme & Abstracts Department of Polymer Engineering University of Minho
 AERC 2003 EUROPEAN SOCIETY OF RHEOLOGY Portuguese Society of Rheology ...
[www.rheology-esr.org/.../Abstracts/AERC2003_symposiums.pdf?](http://www.rheology-esr.org/.../Abstracts/AERC2003_symposiums.pdf?PHPSESSID=091bf71cb79c004dc4f683fff493547c)

[PHPSESSID=091bf71cb79c004dc4f683fff493547c](#) - Supplemental Result - [Similar pages](#)

[PDF] 2001 BIENNIAL REPORT

File Format: PDF/Adobe Acrobat - [View as HTML](#)

Page 1. Applied Physics Laboratory College of Ocean and Fishery Sciences
 University of Washington 2001 BIENNIAL REPORT Page 2. The ...

www.apluw.com/downloads/2001_biennial.pdf - Supplemental Result - [Similar pages](#)

[PDF] [Fluid Mechanics](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... Introduction and Scope • Boundary Layers • **Drag** • Lift • Boundary ... 3-197 Introduction • Experimental Techniques • **Surface Roughness**, Adhesion, and ...

www.bgu.ac.il/~yakhof/mf2/Fluid_Dynamics.pdf - Supplemental Result - [Similar pages](#)

[PDF] [Modern Manufacturing](#)

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... For example, generally achievable **surface roughness** for sand casting is 400 to 800 ...

Higher speeds cause **vibration**, which makes use of a mechanical transmission ...

www.itiomar.it/publica/dispense/MECHANICAL%20ENGINEERING%20HANDBOOK/Ch13.pdf - Supplemental Result - [Similar pages](#)




Result Page: [Previous](#) [1](#) [2](#) [3](#) [Next](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google



Web Results 21 - 25 of about 28 for **drag vortex vibration ks/d OR k/d "surface roughness"**. (0.16 seconds)

[PDF] W OrcaFlex Manual

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 59 3.14 M - VIV 59 3.14.1 M01 **Vortex** Tracking 59 4 USER INTERFACE ... 151 6.9.2 RAO Quality Checks 152 6.9.3 **Drag** Loads 154 6.9.4 Stiffness, Added Mass and Damping ...

www.orcina.co.uk/OrcaFlex/OrcaFlex.pdf - Supplemental Result - [Similar pages](#)

[PDF] W OrcaFlex Manual

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 61 3.14 M - VIV 61 3.14.1 M01 **Vortex** Tracking 61 4 USER INTERFACE ... 159 6.9.2 RAO Quality Checks 161 6.9.3 **Drag** Loads 162 6.9.4 Stiffness, Added Mass and Damping ...

www.orcina.co.uk/OrcaFlex/OrcaFlex_US_paper_size.pdf - Supplemental Result - [Similar pages](#)

[PDF] DEPARTMENT OF DEFENSE TEST METHOD STANDARD FOR ENVIRONMENTAL ...

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... 513.5-1 - 513.5-14 514.5 **Vibration** } } } } 514.5-i - 514.5C-16 ... 518-1 - 518-6 519.5 Gunfire **Vibration** } } } } ...

combatindex.com/mil_docs/pdf/std/0800/MIL-STD-810F.pdf - Supplemental Result - [Similar pages](#)

Army FY04.3 SBIR Solicitation Topics

L. Sundkvist, Laser radar for non-contact **vibration** measurements and as part ...

The tables, which detail lift, **drag**, and pitching moment as a function of ...

citti.uccs.edu/solicitations/army04sbir3.html - 2565k - [Cached](#) - [Similar pages](#)

[PDF] ARMY - 1 US ARMY SUBMISSION OF PROPOSALS Topics

File Format: PDF/Adobe Acrobat - [View as HTML](#)

... EMI Suppression Technology (CREST) A04-081 Automated Air Traffic Control (ATC) A04-082 Advanced Flow Control Actuators for Fuselage **Drag** Reduction A04-083 ...

<https://www.dodsbir.net/solicitation/sbir043/pdf/army043.pdf> - Supplemental Result - [Similar pages](#)

In order to show you the most relevant results, we have omitted some entries very similar to the 25 already displayed.

If you like, you can repeat the search with the omitted results included.



Result Page: [Previous](#) [1](#) [2](#) [3](#)

[Search within results](#) | [Language Tools](#) | [Search Tips](#)

[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google


[Web](#) [Images](#) [Groups](#) [News](#) [Froogle](#) [Local](#) [more »](#)

drag viv vortex vibration roughness surface ks/

Search

[Advanced Search](#)
[Preferences](#)
[Get the Google Toolbar](#)

Web

Results 1 - 6 of 6 for **drag viv vortex vibration roughness surface ks/d OR k/d**. (0.25 seconds)

Tip: Save time by hitting the return key instead of clicking on "search"

[PDF] [Microsoft PowerPoint - Some of the VIV R&D Activities at Shell.ppt](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)VIV suppression general. • Fairings. • Strakes. • **Surface roughness** ...Allen, DW, Henning DL, and Lee, L., 2004, "**Vortex-induced vibration** current tank ...www.marin.ntnu.no/~callas/workshop/VIVW_Lee_Shell.pdf - [Similar pages](#)[Sleeve or coating - Patent Storm](#)Apparatus for controlling **drag** and **vortex-induced vibration** exerted onto a ...having a **surface roughness** coefficient of **K/D** less than or equal to 1×10^{-4} , ...www.patentstorm.us/class/405/216-Sleeve_or_coating.html - 34k - [Cached](#) - [Similar pages](#)[PDF] [DIS Submission to ISO CS 2004-08-31](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)A.9.5.2.3.2 **Surface roughness**. The dependence of the steady-flow **drag** coefficient at... response called **vortex induced vibration (VIV)** can occur. ...www.galbraithconsulting.co.uk/iso/19902/DIS_text/19902_Clause_09_DIS.pdf - [Similar pages](#)[PDF] [W OrcaFlex Manual](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)... 59 3.13.1 Example RAO Text File 59 3.14 M - **VIV** 59 3.14.1 M01 **Vortex** Tracking 594 USER INTERFACE 61 ... 174 6.10.18 **Drag** Chains 176 6.10.19 Line End Conditions ...www.orcina.co.uk/OrcaFlex/OrcaFlex.pdf - Supplemental Result - [Similar pages](#)[PDF] [W OrcaFlex Manual](#)File Format: PDF/Adobe Acrobat - [View as HTML](#)... 4 3.13.1 Example RAO Text File 61 3.14 M - **VIV** 61 3.14.1 M01 **Vortex** Tracking 614 USER INTERFACE 63 ... 184 6.10.18 **Drag** Chains 186 6.10.19 Line End Conditions ...www.orcina.co.uk/OrcaFlex/OrcaFlex_US_paper_size.pdf - Supplemental Result - [Similar pages](#)[00databasealphabet I+pw u 00databaseinfo B0 FL 00databasescript I+ ...](#)

... BQ9G y carat BQ94 T caravan BQ+L Z caravel BQ+k d caraway BQ/B i carbamide BQ/j

... U **surface** HqHR BP **surface** finish Hqlg 7 **surface** plate HqJb w **surface** ...users.csu.ac.ru/~srg/dicts/sokrat_en-ru.index - 970k - [Cached](#) - [Similar pages](#)

drag viv vortex vibration roughness s

Search

[Search within results](#) | [Language Tools](#) | [Search Tips](#) | [Dissatisfied?](#) [Help us improve](#)
[Google Home](#) - [Advertising Programs](#) - [Business Solutions](#) - [About Google](#)

©2005 Google